AIKO

NEOSTAR

3S60 Mono-Glass Module

520W-545W



Technical Features:

- Partial Shading Optimisation
- Better Temperature Coefficient
- High Temperature Restriction
- Micro-crack Resistance
- Higher Power
- Lower BOS
- More Aesthetic Values
- Infinite Technology

TIER 1 BloombergNEF

ESG TRANSPARENCY AWARD 2023/24 EXCELLENCE

inter solar award 2023 WINNER

reddot winner 2023

Warranty partner

Munich RE

CE

TÜVRheinland

25 year Product Warranty

30 year Performance Warranty

IEC61215/IEC61730
IEC61701/IEC62716


ISO9001:ISO Quality Management System
ISO14001:ISO Environmental Management System
ISO14064:Greenhouse Gas Verification Statement
ISO45001:ISO Occupational Health and Safety Management System


Neostar 3S60

AIKO-A-MCE60Mb

545W	24.6%	≤1%	≤0.35%
Output	Efficiency	First-year Degradation	Annual Degradation from Year 2-30

30-year Linear Performance Warranty





Tolerance
L: ±2mm
W: ±2mm
Unit: mm

Electrical Characteristics (STC: AM1.5 1000W/m² 25℃ NOCT: AM1.5 800W/m² 20℃ 1m/s) Power Tolerance:0~ + 3%

Module Type	AIKO-A520-MCE60Mb		AIKO-A525-MCE60Mb		AIKO-A530-MCE60Mb		AIKO-A535-MCE60Mb		AIKO-A540-MCE60Mb		AIKO-A545-MCE60Mb	
Test Conditions	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Pmax [W]	520	394	525	398	530	402	535	405	540	409	545	413
Voc [V]	45.20	42.88	45.30	42.98	45.40	43.07	45.50	43.17	45.60	43.26	45.70	43.36
Vmp [V]	38.00	36.05	38.10	36.15	38.20	36.24	38.30	36.34	38.40	36.43	38.50	36.53
Isc [A]	14.69	11.87	14.72	11.89	14.76	11.93	14.80	11.96	14.84	11.99	14.88	12.02
Imp [A]	13.69	10.94	13.79	11.02	13.88	11.10	13.97	11.17	14.07	11.25	14.16	11.32
Module Efficiency	**23.5%**		**23.7%**		**23.9%**		**24.1%**		**24.4%**		**24.6%**	

Product Specification

Cell Type	N-Type ABC
Front Cover Mono glass	3.2 mm tempered glass
Backsheet	High weather resistant backsheet
Frame	Black Anodized aluminum
Cable	4mm²(IEC) 12AWG(UL) ±1200mm
No. of Cells	120(6*20)
Junction Box	IP68, 3 bypass diodes
Connector	Original MC4-EVO2A
Weight	23.2kg±3%
Dimension	1954*1134*30mm
Package Detail	37pcs per pallet / 185pcs per 20'GP / 888pcs per 40'HC

Temperature Ratings (STC)

Temperature Coefficient of Isc	+ 0.05%/ ℃
Temperature Coefficient of Voc	- 0.22%/ ℃
Temperature Coefficient of Pmax	- 0.26%/ ℃

Installation Guide

Operation Temperature	-40℃ - +70℃
Maximum Series Fuse Rating	25A
Protection Class	Class II
Maximum System Voltage	DC1500V
Maximum Static Loading	Front 5400Pa Back 2400Pa
Hail Test	25 mm diameter hail at 23 m/s
Fire Rating	IEC Class C

www.aikosolar.com
marketing@aikosolar.com

*AIKO reserves right to update the specification without notice
*Optional Munich Re coverage is available upon request

202604_V3.1_EN